

# POLYESTER FLEECE 60g

## Polyester fleece for reinforcing waterproofing membranes

### Description - Fields of application

Polyester fleece of 60 g/m<sup>2</sup>. It is used in order to locally or totally reinforce waterproofing coatings (e.g. for ISOFLEX, ISOFLEX-T25, ISOFLEX-PU 500, AQUAMAT-ELASTIC membranes, etc.), in case the surface shows local or total cracks, as well as at wall-to-floor junctions, corners, etc.

### Packaging

1m x 50m rolls (50 m<sup>2</sup>), 10cm x 50m rolls.

### Storage

Stored in its original, unopened packaging, protected from humidity and UV radiation.

### Technical data

Property		Unit	Value
Weight		g/m <sup>2</sup>	60
Thickness		mm	0.62
Tensile strength	MD	N/5cm	14
	CD	N/5cm	12
Elongation at break	MD	%	40
	CD	%	50

### ISOMAT S.A.

BUILDING CHEMICALS AND MORTARS

**Thessaloniki:** 17<sup>th</sup> km Thessaloniki - Ag. Athanasios

P.O. BOX 1043, 570 03 Ag. Athanasios

Tel.: 2310 576 000 Fax: 2310 722 475

**Athens:** 57<sup>th</sup> km Athens-Lamia National Road, 32011 Inofita

Tel.: 22620 56 406 Fax: 22620 31 644

[www.isomat.eu](http://www.isomat.eu) e-mail: [info@isomat.eu](mailto:info@isomat.eu)