

Primer of ISOFLEX-PU

Description

One component, polyurethane primer with solvents. It ensures the proper adhesion of the brushable, elastomeric liquid membrane ISOFLEX-PU, when waterproofing terraces with porous substrates. By penetrating inside the pores of the substrate, it acts as a bonding layer between ISOFLEX-PU and the substrate.

Fields of application

PRIMER-PU is used as a primer for securing the adhesion of ISOFLEX-PU on substrates like concrete, cement-mortars, wood etc.

Technical data

Form: pre-polymer polyurethane
Color: transparent
Successive layer: after 1-3 h

Directions for use

1. Substrate

The surface to be primed must be dry, free of dust, grease, dirt etc.

2. Application

PRIMER-PU is thoroughly stirred and uniformly applied on the substrate by brush, roller or spraying, before the application of ISOFLEX-PU.

Consumption

200-300 g/m², depending on the absorptivity of the substrate.

Packaging

PRIMER-PU is available in tin buckets of 5 kg and 17 kg.

Storage

Shelf-life in sealed containers is at least 9 months, in frost free and dry conditions.

Remarks

- Temperature during the application and hardening of the product should be between +5°C and +35°C.
- Unsealed packages shall be used at once and cannot be restored.

ISOMAT S.A.

BUILDING CHEMICALS AND MORTARS

MAIN OFFICES - FACTORY:

17th km Thessaloniki - Ag. Athanasios Road,
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece,
Tel.: +30 2310 576 000, Fax: +30 2310 722 475

www.isomat.net e-mail: info@isomat.net